

Inventors: Thomson et al. Docket No: M&G 50037.0212US01



Title: METHOD AND SYSTEM FOR AUTOMATICALLY DISPLAYING CONTENT OF A WINDOW

ON A DISPLAY THAT HAS CHANGED ORIENTATION

Inventors: Thomson et al. Docket No: M&G 50037.0212US01



Inventors: Thomson et al. Docket No: M&G 50037.0212US01




Fig. 3

Inventors: Thomson et al. Docket No: M&G 50037.0212US01







Fig. 4

Inventors: Thomson et al. Docket No: M&G 50037.0212US01







Inventors: Thomson et al. Docket No: M&G 50037.0212US01




Fig. 6

Inventors: Thomson et al. Docket No: M&G 50037.0212US01

7/10




Fig. 7

Inventors: Thomson et al. Docket No: M&G 50037.0212US01




Fig. 8

Inventors: Thomson et al. Docket No: M&G 50037.0212US01




Fig. 9

Inventors: Thomson et al. Docket No: M&G 50037.0212US01

```
hwnd:
      window handle of the window
      wParam:
      WMSCD_DIALOGSCROLLBAR - message used by the shell to add/remove
      scrollbars on a display screen orientation change.
      This will be defined in public\common\oak\inc\pwinuser.h as:
      #define WMSCD_DIALOGSCROLLBAR
                                               0x02
      IParam:
      pCopyDataStruct = (COPYDATASTRUCT*) | Param
      If pCopyDataStruct->dwData == TRUE the vertical scrollbar will be added
      If pCopyDataStruct->dwData == FALSE the vertical scrollbar will be
      removed
      prcClient = (RECT*) pCopyDataStruct->lpData
      prcClient points to client rect of window in client coordinates that window
      manager will use to compute the viewable area the end user will be able to
      scroll to. The shell should use the client rect of the window before the shell
      resizes the window.
      Return Value:
      TRUE if succeeded to remove/add the scrollbar
      FALSE if failed to remove/add the scrollbar
      Here is sample code that uses this message:
1000
      hwnd = FindWindowThatNeedsToBeResizedBecauseOfScreenRotation();
      if(hwnd)
         COPYDATASTRUCT
1010
                              cds:
        GetClientRect(hwnd, &rcBuffer);
1020
       `cds.dwData = TRUE;
 1030
      cds.cbData = sizeof(RECT);
 1040 cds.lpData = &rcBuffer;
        // shrink the height by 80 pixels
1050
        SetWindowPos(hwnd, 0, 0, 0, rcBuffer.right - rcBuffer.left,
      rcBuffer.bottom - rcBuffer.top - 80,
      SWP_NOZORDER|SWP_NOACTIVATE|SWP_NOMOVE);
       // use timeout in case app is hung
       Iret = SendMessageTimeout(hwnd, WM_SYSCOPYDATA)
      WMSCD_DIALOGSCROLLBAR, (LPARAM)&cds, SMTO_NORMAL, 1000,
      &dw);
      }
```